



INSTRUCTIONS FOR ASSEMBLY OF GRANITE GALLERY BENCHES

Package contents: 2 x Granite End Supports, 1 x Teak Seat Section, 1 x Adhesive Glue Tube

The bench should be assembled in location and is not designed to be moved once assembled.

A minimum of 3 people are required for safe assembly.

1. Stand the granite end sections (A & B) upright with seat slots facing each other and at a distance slightly further apart than the length of the seat section.
2. Using the adhesive dispenser provided apply a line of adhesive glue along the lower and upper rear edge of the cut-out pocket section of each granite slab.

Do not apply too much and run the adhesive to within 15-20mm from the ends of the granite - this will ensure the adhesive doesn't squeeze out of the ends when the seat section is placed.

Please Note: This adhesive is to prevent the teak bench section from sliding back and forward. It is not intended as a structural adhesive.

3. Insert one end of the seat section (C) into the slot of one of the granite end sections ensuring that it beds into the adhesive. Once correctly in place one person should remain to hold the granite slab and seat section in position.
4. With the glued section supported, carefully manoeuvre the remaining granite end section into place again ensuring that it beds into the adhesive. It is recommended that two people move the remaining granite section into place.
5. Ensure that each granite end slab is sitting vertically at 90° and the seat is level - for best results use a spirit level. Please allow 24 hours for the adhesive to set.

General Note

You may find it helpful to use some timber batons on which to rest the granite end sections during assembly. These can be removed once assembly is completed. Using batons can reduce the risk of damage to the base edges of the granite, particularly when assembling on a stone or similar surface.

Caution

- Each Granite end support weighs more than 70 kgs. Do not attempt to lift or move this on your own. A minimum of two people should lift each granite section.
- Do not attempt to lift by bending forward. Bend your hips and knees to squat down and straighten your legs to lift.
- It is strongly recommended that you wear the appropriate protective gloves and footwear to minimise risk of injury.
- Be careful when manoeuvring the granite supports otherwise there is a risk of damage to the edges which can chip easily if brought into contact with another hard material (e.g Stone, Concrete etc.)